ENEOS FORK OIL

Premium High-Performance Suspension Fluid

ENEOS Fork Oil is a premium fluid engineered for motorcycle forks, blending selected base oils with advanced additives. Its formulation delivers exceptional hydraulic springing and shock absorption, while ensuring smooth fork movement and minimal wear. The oil's low pour point, high viscosity index, and thermal stability allow for consistent performance across a wide temperature range. It offers robust protection against foaming and corrosion, maintains seal compatibility, and resists viscosity breakdown over time – all qualities that make this product an ideal choice for riders seeking reliable, long-lasting fork performance in various riding conditions stability.

SPECIAL FEATURES

1. Advanced Friction-Reducing Technology
ENEOS Fork Oil is formulated with an exclusive anti-friction additive that minimizes drag and ensures smoother sliding action within the fork system. This advanced technology enhances riding comfort and optimizes suspension performance, providing precise handling and improved control for a superior riding experience.

2. Thermal Stability & Consistent Absorption
Delivers exceptional thermal stability, ensuring consistent viscosity and damping performance across a wide temperature range. Whether during cold starts or high-temperature riding conditions, ENEOS Fork Oil maintains reliable fork response and absorption characteristics, making it ideal for diverse riding environments.

3. Superior Protection & Longevity
Designed for durability, ENEOS Fork Oil offers excellent compatibility with fork seals, preventing leaks and extending the lifespan of suspension components. Its anti-wear, anti-corrosion, and anti-foaming properties ensure long-lasting protection while maintaining smooth fork operation, even under demanding conditions.

APPLICATION

- Suitable for many types of motorcycle forks.
- Available in **10W** and **15W** viscosity grades for customized damping response based on riding style and road conditions.

CONTAINERS

1L

TYPICAL PROPERTIES

	10W	15W
Density (15°C), g/cm^3	0.8583	0.8548
Kinematic viscosity		
(40°C), mm^2/s	30.71	43.9
(100°C), mm^2/s	5.964	7.6
Viscosity index	143	141
Flash point (COC), °C	223	218
Pour point, °C	–39.0	–45.0

Note: The typical properties may be changed without notice. (March 2025)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEGDE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR, NEGLIGENCE AND INACCURACIES IN THIS INFORMATIONSHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APLLIED HERE.