Product Information

ENEOS PRO-Plus 10W-40

Synthetic Performance Engine Oil

ENEOS PRO-Plus 10W-40 is the high performance, synthetic and all-season motor oil engineered for the toughest requirements of modern, high-performance gasoline and diesel engines in normal and extended drain intervals. Applicable for use in gasoline and diesel engines, in vehicles with or without catalytic converters and turbochargers. Designed for optimal wear protection and protecting sealing materials and thus protecting engines from leakages. This is high performance engine oil offering enhanced lubrication especially for older vehicles and especially suitable for vehicles with higher mileages over 60.000km. This oil assures excellent cold start with outstanding lubricating film at high temperatures. This oil takes care of trouble-free functioning of the engine, because of the chosen additive package. In addition, together with the excellent detergent/dispersant properties, this oil ensures a clean and reliable engine.

SPECIAL FEATURES

1. Synthetic Motor Oil

ENEOS PRO-Plus 10W-40 is all-year oil for gasoline and diesel engines, engineered for vehicles with or without catalytic converters and turbochargers. This oil is blended from synthetic base oils and optimized additives to provide optimal lubrication at low temperatures, outstanding engine cleanliness, seals protection and high shear stability. This oil is especially recommended for maintaining optimal engine condition in older vehicles and especially vehicles with mileages over 60,000 km. This oil is proven superior to motor oils made from mineral base oils.

2. Reducing Fuel consumption

ENEOS PRO-Plus 10W-40 helps reducing the fuel consumption as well as reducing emission levels. Because of the unique formulation a low evaporation under severe operating conditions is guaranteed.

3. Excellent Resistance to Wear, Corrosion, Foaming and Oxidation

ENEOS PRO 10W-40 gives optimum protection against wear and has strong anti-corrosion and anti-foam characteristics as well as high resistance against oxidation. It offers increased lubrication reliability and smooth engine operating under all driving conditions.

RECOMMENDATIONS & SPECIFICATIONS

- API SN
- ACEA: A3/B4
- VW 501.01/505.00

APPLICATION

Motor oil for gasoline and diesel engines of Cars and Commercial vehicles including Minibuses & Trucks

PACK SIZES

1L, 4L, 20L, 60L, 208L drum and 1000L IBC

TYPICAL PROPERTIES

SAE viscosity grade	10W-40
Density (15°C), g/cm^3	0.87
Flash point (COC), °C	226
Kinematic viscosity (40°C), mm^2/s	97.8
(100°C), mm^2/s	14.8
Viscosity index	158
Pour point, °C	–39.0
HTHS Viscosity (150°C), mPA.s	4.04
TAN mgKOH/g	2.33
TBN mgKOH/g	10.4

Note: The typical properties may be changed without notice. (November 2024)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEGDE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR NEGLIGENCE AND INACCURACIES IN THIS INFORMATIONSHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APLLIED HERE.