Product Information

ENEOS GRAND-AGRI 10W-40

Cutting-Edge Super Tractor Oil Universal (STOU)

ENEOS GRAND-AGRI 10W-40 is a high-performance Super Tractor Oil Universal (STOU), formulated using multipurpose additive synthetic technology to meet the demands of agricultural machinery. This advanced lubricant delivers top-tier protection and efficiency for final drives, hydraulic systems, wet brakes, clutches, transmissions and engines in tractors and farm equipment. With its exceptional versatility, it is also suitable for older engines that do not incorporate aftertreatment devices, making it a reliable and compatible solution for a wide range of agricultural applications.

SPECIAL FEATURES

1. Advanced Protection & Performance

ENEOS GRAND-AGRI 10W-40 is engineered to deliver smooth operation and exceptional durability across critical components, including transmissions, differentials, and hydraulic systems. Its superior anti-wear and anti-oxidation properties minimize component wear, reduce deposit buildup, and extend the lifespan of agricultural machinery. Designed for demanding environments, this lubricant ensures consistent performance under extreme conditions, such as heavy loads and fluctuating temperatures.

2. Versatile Multipurpose Application

This high-performance oil is tailored for use in final drives, hydraulic systems, wet brakes, clutches, transmissions and engines in agricultural equipment. Its shear-stable formulation maintains optimal viscosity over extended periods, ensuring reliable performance in diverse farming operations. ENEOS GRAND-AGRI 10W-40 is fully compatible with a wide range of machinery, including tractors and other farm equipment, making it a versatile solution for agricultural needs.

3. Enhanced Equipment Efficiency & Reliability

With exceptional thermal stability, ENEOS GRAND-AGRI 10W-40 prevents oxidation and viscosity breakdown, reducing the risk of overheating and wear on critical components. It ensures smooth hydraulic system operation and reliable wet brake performance, minimizing noise and vibrations. Additionally, its anti-corrosion and anti-foaming properties promote long-term operational efficiency while reducing maintenance costs, ensuring dependable performance for agricultural machinery.

RECOMMENDATIONS & SPECIFICATIONS

- API CG-4/SF/GL-4
- ACEA E2
- ZF TE-ML 06B/07B
- CNHi M2C-159B/159C
- Allison C-4
- John Deere J27
- GIMA M1145
- Caterpillar TO-2
- Daimler MB 228.1/227.1
- CCMC D4/G2

APPLICATION

- Ideal for use in tractors and agricultural machinery requiring a STOU-type lubricant.
- Suitable for older tractor models that do not utilize aftertreatment systems.
- Recommended for final drives, hydraulic systems, wet brakes, clutches, transmissions and engines.

PACK SIZES

20L, 60L, 208L

TYPICAL PROPERTIES

SAE viscosity grade	10W-40
Density (15°C), g/cm^3	0.8682
Flash Point, °C	232
Kinematic viscosity (40°C), mm^2/s	83.91
(100°C), mm^2/s	13.01
Viscosity index	155
CCS Viscosity(-20°C), mPa.s	5888
Pour point, °C	-36.0
TAN mgKOH/g	2.21
TBN mgKOS/g	11.8

Note: The typical properties may be changed without notice. (March 2025)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEGDE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR, NEGLIGENCE AND INACCURACIES IN THIS INFORMATIONSHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APLLIED HERE.