Product Information

ENEOS GRAND-AGRI 15W-40

Premium Super Tractor Oil Universal (STOU)

ENEOS GRAND-AGRI 15W-40 is a high-performance Super Tractor Oil Universal (STOU) lubricant, engineered to meet the demanding requirements of agricultural machinery. This multi-functional, heavy-duty formulation provides exceptional oxidation resistance, enhanced wear protection, and effective soot dispersion, ensuring reliable operation and extended service life. Designed to maximize equipment uptime, reduce maintenance costs, and promote efficient operations, this versatile lubricant is the ideal solution for a wide range of agricultural applications, including engines, final drive, transmissions, hydraulics, and wet brake systems.

SPECIAL FEATURES

1. Advanced Wear Protection & Oxidation Resistance

ENEOS GRAND-AGRI 15W-40 is formulated to deliver exceptional wear protection, reducing friction and extending the lifespan of critical components in agricultural machinery. Its high oxidation resistance prevents sludge formation and deposit buildup, ensuring engine cleanliness and maintaining operational efficiency. Even under heavy loads and extreme temperature conditions, this lubricant ensures smooth and reliable performance, making it ideal for demanding farming applications.

2. Multi-Purpose Versatility

This multi-functional lubricant is specifically designed for use in final drives, hydraulic systems, wet brakes, clutches, transmissions and engines of tractors and other agricultural equipment. It is compatible with both modern and older engines, offering a versatile solution for a wide range of farming machinery. ENEOS GRAND-AGRI 15W-40 provides dependable performance across diverse agricultural environments, reducing the need for multiple lubricants and simplifying maintenance operations.

3. Enhanced Equipment Efficiency & Durability

The optimized formulation of ENEOS GRAND-AGRI 15W-40 helps reduce maintenance costs by prolonging service intervals and protecting against corrosion, foaming, and viscosity breakdown. Its advanced properties maintain hydraulic stability, enabling efficient power transfer and ensuring smooth wet brake engagement. This results in improved equipment efficiency, reliability, and long-lasting durability for agricultural machinery under tough working conditions.

RECOMMENDATIONS & SPECIFICATIONS

- API CG-4/SF/GL-4
- ACEA E2
- ZF TE-ML 06B/07B
- CNHi M2C-159B/159C
- Allison C-4
- John Deere J27
- GIMA M1145
- Caterpillar TO-2
- Daimler MB 228.1/227.1
- CCMC D4/G2

APPLICATION

- Recommended for agricultural machinery requiring STOU-type lubricants.
- Compatible with older agricultural equipment without aftertreatment systems.
- Ideal for use in engines, final drives, transmissions, hydraulic systems, and wet brakes.

PACK SIZES

20L, 60L, 208L

TYPICAL PROPERTIES

SAE viscosity grade	15W-40
Density (15°C), g/cm^3	0.8811
Flash Point, °C	234
Kinematic viscosity (40°C), mm^2/s	94
(100°C), mm^2/s	13.21
Viscosity index	139
CCS Viscosity(-20°C), mPa.s	5784
Pour point, °C	-33.0
TAN mgKOH/g	2.32
TBN mgKOS/g	11.62

Note: The typical properties may be changed without notice. (March 2025)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEGDE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR, NEGLIGENCE AND INACCURACIES IN THIS INFORMATIONSHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APLLIED HERE.